

Evaluation of PCB TMDL Efforts in the Delaware Estuary

New Jersey Clean Water Council

June 10, 2014

Gregory J. Cavallo, PG

Modeling, Monitoring and Assessment Branch




Outline

- Background
- Analytical Methods
- Detection limits and trends in blanks
- PMP key elements and activities
- Point source initiatives
- Trends in point source loadings since 2005
- Non-point source initiatives
- Achieving individual WLA

Background


- Delaware Estuary portion of the Basin is 133 miles long and is bordered by DE, NJ and PA.
- It consists of 5 water quality management units called Zones.
- EPA Regions II & III establish Stage 1 TMDLs for Zones 2 – 5 in December 2003.
- EPA Regions II & III establish Stage 1 TMDL for Zone 6 in December 2006.



PCB Chemistry

- Man-made organic chemicals with a biphenyl base structure and 209 possible chlorine substitution patterns.
- Terminology: Aroclors, congeners, homologs.
- Properties: Hydrophobic, tend to accumulate in sediments and tissues

PCB Structure and Terminology



Homolog	# of congeners
Mono	3
Di	12
Tri	24
Tetra	42
Penta	46
Hexa	42
Hepta	24
Octa	12
Nona	3
Deca	1

- Terminology:
 - Aroclors- Commercial mixtures
 - Congeners- Individual compounds (209)
 - Homolog- Group of compounds based on level of chlorination (10)

PCB Toxicity

- Probable Human Carcinogen
- Disrupt hormone function
- Immunosuppressant
 - Like dioxin, PCBs bind to receptors that control immune system function, disturbing the amounts of some immune system elements like lymphocytes and T cells
- Developmental/Neurobehavioral Effects

Analytical and Monitoring Approaches

- DRBC's convened a Data Quality subcommittee to address issues regarding analytical and monitoring approaches.
- Participants included:
 - Industry, Municipal, Academic, Environmental and Laboratory representatives.
- DQ Subcommittee Recommended:
 - Sample identification protocols
 - Sample size and collection methods
 - Analytical methodology
 - Electronic data formatting and reporting


Measuring PCBs

- To develop a more accurate Stage 2 TMDL by requiring better quantification of the concentrations from the various PCB source categories.
- A HRGC/HRMS analytical methodology capable of providing detection limits in pg/L (ppq)
 - EPA Method 1668 Rev. A
- Results:
 - Comparability of analytical results
 - Reduced analytical uncertainty
 - Greater accuracy in estimated loadings
 - More accurate long-term trends analysis
 - Better temporal and spatial evaluation of data

Supporting Documentation

- Adopted Recommendations available at:
 - <http://www.state.nj.us/drbc/quality/toxics/pcbs/monitoring.html>
- Additionally, the Commission in cooperation with select point source dischargers developed an Access database to organize the information.
- Commission maintains the database for all discharge data
- Benefits:
 - Provide a basis for determining effectiveness of pollutant reduction measures.
 - An open and transparent database will provide for direct and candid communication between the regulated community and the regulatory agencies.

PCB Ambient Water Surveys Stage 1 data (2001-2003) vs Stage 2 data (2005-2012) Total PCB Concentrations




Sampling Locations 2004 - 2006

Species

Channel Catfish CC Benthic
White Perch WP Pelagic


Tidal Locations

Crosswicks Creek RM 128
Tacony-Palymra Br. RM 107
Woodbury Creek RM 91
Raccoon Creek RM 80
Salem River RM 58



Total PCBs

2004-2006 (n=3), 209 congeners




Reducing PCB Loadings to the Estuary Pollutant Minimization Plans (PMPs)

- Key PMP Elements
 - Source identification and reduction
 - Monitoring and progress report
 - Remediation activities
- PMP Approaches:
 - Remove PCB transformers and capacitors
 - Trackdown studies to identify and remove sources
 - Contaminated sediment control or removal

Dischargers in PCB TMDL (n=102)


Number of Dischargers




PMP Oversight



1668A Detection Limits by Homolog




Rinsate and Method Blank Results




Commission PMP Activities

- Workshops were provided for dischargers in 2005, 2007 and 2012 to assist in:
 - Preparation and approval of PMPs
 - Preparation and submittal of Annual Reports
 - Illustrate effectiveness of remedial measures
- Training sessions were provided by DRBC for PADEP and NJDEP staff to foster a consistent approach for PMP evaluation.
- Commission staff have provided technical assistance to dischargers and their consultants.
- PMP resources available at:
 - <http://www.state.nj.us/drbc/programs/quality/pmp.html>

2005 Ranked Point Source PCB Concentrations in All Discharges



Ranked Point Source PCB Concentrations



Municipal Initiatives

■ Tinicum Township

- Increased solids removal efficiency at WWTP
- Annual sediment removal at pump stations
- Trackdown studies have identified a major source of PCBs Airport Business Complex (ABC)
 - Sewer line relining to eliminate infiltration

■ Camden County Municipal Authority (CCMUA)

Trackdown studies identified:

- Sewer interceptors with elevated PCB sediment concentrations
- Existing and abandoned industries contributing PCBs.

Coordinating efforts with NJDEP, EPA and City of Camden

Industrial Initiatives

- USX Steel Fairless Hills, PA
 - Removed 700,000 lbs. of PCB transformer oil
 - Removed 440,000 lbs. of PCB debris and capacitors
 - Removed contaminated sediment initiated stormwater control
- Amtrak Wilmington, DE
 - Sediment removal from sewer lines (60 tons)
 - Redesigned stormwater system to reduce direct discharge
 - Considering additional sediment removal

Specific Example


- Calpine Deepwater Energy Facility
 - Legacy contamination (built 1929)
- Two stormwater outfalls monitored
 - PCB transformers removed
 - Catchments and stormwater lines cleaned
 - Geotextile filter baskets and filter guards deployed at drains



Slides courtesy Calpine Energy and Cardno ENTRIX

Deepwater Results


Penta-CB Loading at Deepwater Energy Center Outfall 002



Cumulative Reduction of Penta-CBs: 99.5%


Slides courtesy of Calpine
Energy and Cardno ENTRIX

Penta-CB Loading at Deepwater Energy Center Outfall 017




Cumulative Reduction of Penta-CBs: 98.3%

10 Dischargers Representing 90% of Point Source PCB Loadings in the Estuary



10 Dischargers Representing 90% of Point Source PCB Loadings in the Estuary



Non-Point Sources Success

- Exxon Mobil, Paulsboro NJ
 - 16 acre tidal wetland containing contaminated PCB aluminosilicate pellets
 - Excavated 120,000 tons of material
 - Estimated 30-40,000 lbs. of PCBs removed
- Metal Bank, Philadelphia PA
 - 10 acre industrial site (NPL listed)
 - Excavated 1,500 tons of material
 - Approximately 800 lbs. of PCBs removed



Exxon Mobil Site 2004

406 ft

© 2012 Google

Remedial Efforts 2008-09



Slides Courtesy of Alan
Motter NJDEP



Gloucester Co. - East Greenwich Twp



Approximately
30-40,000 lbs. of
PCBs Removed

Mantua Creek 2010

O&M Requirements

- Why is O&M necessary?
 - Prevention of backsliding i.e. increasing loading after an initial reduction
- Example: US Pipe and Foundry
 - Manufactured iron pipe from recycled and new material
 - Stored scrap metal on-site
 - Legacy site >100 years old
 - Storm water effluent contaminated with PCBs

U.S. Pipe and Foundry (Outfall 004)

Year	PMP Initiatives	Analytical Results
2007	Existing sedimentation basin no treatment	118,923 pg/L
2008	Sediment removed from basin and filtration system added	847 pg/L
2009	Filtration system failed and demolition of facility began	47,651 pg/L
2010	Demolition continues increasing sediment load	94,821 pg/L
2011	Demolition completed and rerouting of additional stormwater to sedimentation basin. Increased sediment trapping in stormwater drains	35,086 pg/L
2012	Filtration system under repair (during sample collection). Identification of remaining potential sources	33,434 pg/L
2013	Filtration system repairs completed. Continued system Maintenance. Begin re-grading and seeding to reduce runoff	1,519 pg/L

Dischargers Approaching Individual WLA

- Degussa Corporation (NPDES #PA0051713)
 - Manufactures inorganic industrial products
 - Discharge is treated by Industrial Waste Water Treatment Plant
 - Neutralized
 - Solids removed
- BP Paulsboro (NJPDES #NJ0005584)
 - Former refinery, since demolished undergoing ground water remediation
 - Discharge is treated by Groundwater Treatment Plant
 - Air stripping
 - Carbon filtration

Summary

- The majority of facilities that are implementing a PMP are reporting lower concentrations/loadings of total PCBs in their discharges.
- The top ten dischargers that contribute 90% of the point source PCB loading have reduced their loadings by 46% since 2005.
- The PMP approach is demonstrating progress in reducing PCB loadings from point source discharges.
- Selected dischargers are close to achieving their WLA
- Continuation of this cooperative approach is an essential component of a long-term strategy to achieve the PCB TMDLs.

Questions?

Gregory J. Cavallo

Modeling, Monitoring and Assessment Branch

gregory.cavallo@drbc.state.nj.us

(609) 477-7270

