



List of Manufacturers of Applicable Products That May Be Used Lieu of Laterals and Filter Material pursuant to N.J.A.C. 7:9A-9.8

7/1/2013

Applicable Manufacturers	Applicable Product(s):	Alternative Invert Elevation (in inches) above the level of infiltration <sup>1</sup>
Eljen Corporation <a href="http://www.eljen.com/">http://www.eljen.com/</a> 125 McKee St. East Hartford, CT 06108 Phone: 800-444-1359 Fax: 860-610-0427	GSF <sup>2</sup> Mantis M <sup>5</sup> Series <sup>2</sup>	
Infiltrator Systems Incorporated <a href="http://www.infiltratorsystems.com">http://www.infiltratorsystems.com</a> 4 Business Park Road; P.O. Box 768 Old Saybrook, CT 06475 Phone: 800-221-4436 Fax: 860-577-7001	Quick4 Plus Standard Low Profile Quick4 Plus Standard Quick4 Plus High Capacity Quick4 Standard Quick4 Standard-W Quick4 High Capacity Standard Sidewinder High Capacity Sidewinder High Capacity H-10 High Capacity H-20 Arc 36 Low Profile ARC 36 ARC 36 High Capacity BioDiffuser 11" Standard BioDiffuser 16" High Capacity EZflow 1203H EZflow 1203H-GEO	9.0 (using periscope adaptor) 8.0 8.0 8.0 8.0 11.5 7.0 11.0 11.0 11.0 7.8 7.3 10.4 6.5 11.3
ICC Flowtech, LLC <a href="http://www.iccflowtech.com">http://www.iccflowtech.com</a> 6005 NC HWY 10 W Hickory, NC 28602 Phone: 1-877-ICC-FLOW Fax: 1-732-683-9911	FTS123H FTS142H	

Footnotes:

- 1 - The inlet invert into the product used in lieu of laterals and/or filter material shall be between 12 and 18 inches above the level of infiltration unless an alternative is specified in this column.  
2 - A minimum of 6-inches of manufacturer specified ASTM C33 sand underneath and along the sides of Eljen products which must be present above the level of infiltration and shall not be considered as part of the Zone of Treatment, Zone of Disposal, Fill Enclosure or the required spacing to the edge of a disposal bed.