CONCEPT A

Least costly resist barrier which provides the least coastal storm surge risk reduction benefits to the study area.

- Approximately 86% of people in the study area receive flood risk reduction benefits.
- 8,100 to 8,400 linear feet of structure and 21 gates.
- North Waterfront takes Boathouse into account.
- North Hoboken on-street protection provided along Garden Street until elevation tie-in.
- Hoboken Terminal does not receive flood risk reduction benefits.
- South Waterfront constructed independent of Longslip Canal.
- Permanent movable gates proposed to address flood risk reduction along the underpass.

Legend:

Gate - Sliding

Sate - Swinging

Deployable Flood Wall

Landscape

Berm

Revetment

Raised Path

Seawall

Flood Wall

T Wall Ramp

— Municipal Boundaries

--- Study Area


--- Ferry Lines

Preliminary FEMA 100 year Flood Plain


MIN DFE: Approx. Min. FEMA Certification

MAX DFE: Approx. 500 Year + 2075 NOAA SLR

*All DFE's are Approximate and Subject to Change







CONCEPT B

High coastal storm surge risk reduction with substantial resist **structure construction** in the northern study area.

- Approximately 98% of people in the study area receive flood risk reduction benefits.
- 13,430 linear feet of resist structure and 21 gates.
- Weehawken tie-in at Lincoln Tunnel.
- Permanent built structures on North Waterfront provide flood risk reduction benefits.
- Hoboken Terminal does not receive flood risk reduction benefits.
- South Waterfront constructed independent of Longslip Canal.
- Permanent movable gates proposed to address flood risk reduction along the underpass.

Legend:

Gate - Sliding

Sate - Swinging

Deployable Flood Wall

Landscape

Berm

Revetment

Raised Path

Seawall

Flood Wall

T Wall Ramp

Municipal Boundaries

--- Study Area


--- Ferry Lines

Preliminary FEMA 100 year Flood Plain

MIN DFE: Approx. Min. FEMA Certification MAX DFE: Approx. 500 Year + 2075

NOAA SLR

*All DFE's are Approximate and Subject to Change















High

High

High

CONCEPT C

Highest construction costs which provide highest coastal storm surge risk reduction using free-standing, inwater revetments.

- Approximately 99% of people in the study area receive flood risk reduction
- 14,730 linear feet of on land structures with 16 gates
- 2,700 linear feet of in-water resist barriers with 5 gates.
- An in-water revetment is planned in Weehawken Cove, and to the North a Lincoln Tunnel tie-in.
- Permanent built structures on North Waterfront provide flood risk reduction benefits.
- Programmed Bulkheads offer added community benefits, while providing flood risk reduction benefits to those on the water
- South Waterfront constructed assuming the proposed construction of the Longslip Canal project.
- Hoboken Terminal does receive flood risk reduction benefits; resist portion is planned in-water in front of the Terminal.
- Permanent movable gates proposed to address flood risk reduction along the underpass.

Legend:

Gate - Sliding



Deployable Flood Wall



Landscape



Revetment



Seawall



T Wall



Ramp

Municipal Boundaries

--- Study Area


--- Ferry Lines

Preliminary FEMA 100 year Flood Plain

MIN DFE: Approx. Min. FEMA Certification

MAX DFE: Approx. 500 Year + 2075 NOAA SLR

*All DFE's are Approximate and Subject to







99

18

Yes

Yes

Yes

Yes

Yes

Highest

CONCEPT D

High construction cost which provides highest coastal storm surge risk reduction with no free standing, in-water revetments.

- Approximately 99% of people in the study area receive flood risk reduction benefits.
- 16,230 linear feet of resist structure and
 20 gates.
- North Resist portion offers Lincoln Tunnel Tie-In.
- Permanent built structures on North Waterfront provide flood risk reduction benefits
- Programmed Bulkheads offer added community benefits, while providing flood risk reduction benefits to those on the water.
- South Waterfront constructed assuming the proposed construction of the Longslip Canal project.
- Alignment goes through Hoboken Terminal, offering flood risk reduction benefits to essential electrical and utility assets (allows for continued operations in the case of an event).
- Permanent movable gates proposed to address flood risk reduction along the underpass.

Legend:

Gate - Sliding

Sate - Swinging

Deployable Flood Wall

Landscape

Berm

Revetment

Raised Path

Seawall

Flood Wall

T Wall

Ramp

— Municipal Boundaries

--- Study Area


--- Ferry Lines

Preliminary FEMA 100 year Flood Plain


MIN DFE : Approx. Min. FEMA Certification

MAX DFE : Approx. 500 Year + 2075 NOAA SLR

*All DFE's are Approximate and Subject to Change







Population with Coastal Storm Surge Risk Reduction

Flood Risk Reduction

Benefits

Potential

Potential to Adapt to Higher Coastal Flood Event [≥ 500yr and Sea Level Rise]

Rainfall

Built Environment

Waterfront

Potential Community Benefits

Connectivity/ Circulation

Construction/ Maintenance & Operation

Constructability

Maintenance and Operation for Overall System

Environmental Impacts
Potential

Waste Sites (Resist Only)

Wetlands

Yes

Essential Fish Habitat Yes

Threatened and Endangered Species

Army Corp. Permits

Historic Properties Yes

Yes

Archaeological Resources

Benefit/Cost Analysis
Benefits
Highest

Costs Highest

CONCEPT E

Moderate coastal flood risk reduction benefits within the study area at moderate cost.

- Approximately 90% of people in the study area receive flood risk reduction benefits.
- 12, 010 linear feet of resist structure and 16 gates.
- North Waterfront takes Boathouse into account.
- North Hoboken on-street protection provided along Hudson Blvd (Option 1) and Shipyard Lane (Option 2) until elevation tie-in.
- Some programmed bulkhead and other resist structures proposed along South Waterfront.
- Permanent movable gates proposed to address flood risk reduction along the underpass.

Legend:

Gate - Sliding

Gate - Swinging

Deployable Flood Wall

Landscape

Berm

Revetment

Raised Path

Seawall

Flood Wall

T Wall

Municipal Boundaries

--- Study Area


--- Ferry Lines

Preliminary FEMA 100 year Flood Plain

MIN DFE : Approx. Min. FEMA Certification


MAX DFE : Approx. 500 Year + 2075 NOAA SLR

*All DFE's are Approximate and Subject to Change

















•	Waterfront Access		
	Potential Community Benefits		•
- F 1	Connectivity/ Circulation	•	•
	Environmental Justice Populations		
	Construction Maintenance Operation		
	Constructability		

	Construction Duration		
	Maintenance and Operation for Overall System		•
200	Environment Impacts	al	
7	Platem tielus Wastedous Waste Sites	30	30

-	(Resist Only)		
	Wetlands	Yes	Yes
-	Essential Fish Habitat	Yes	Yes
	Threatened		

and Endangered Species	Yes	Yes	
Army Corp. Permits	Yes	Yes	
Historic Properties	Yes	Yes	

Historic Properties	Yes	Yes
Archaeological Resources		

Benefit/Cost Analysis		
Benefits	High	High
Costs	High	High

DELAY STORE DISCHARGE

OVERALL STRATEGY

- Design proposal aims to maximize the potential to capture, store, infiltrate, evaporate, and release stormwater.
- Goal is to achieve community co-benefits while improving management of stormwater that could reduce rainfall flooding.
- Besides BASF site, all stormwater management strategies are entirely on publicly-owned land.
- Proposal uses both "green" and "grey" stormwater management strategies.
- The team considered physical, environmental and infrastructure constraints in locating and designing specific interventions.

Legend:

- Delay + Store Parks
- Water Storage Sites
- Catchment Area
- New Outfall Pipe
- New Storm Sewer Pipe
- + Hybrid Tank
- **Tank**
- Tank Bumpout
- Ongoing Projects
- Existing Flooding "Hotspot"
- Municipal Boundaries
- - Study Area
- --- Ferry Lines

